



Anschluß
Connection

Verschlußstopfen G 1/4
(2 Stück erforderlich)
Sealing plug G 1/4
(2 pieces required)

FAD03/350-FM
Differenzdruckmanometer
Differential pressure gauge

FAD03/350C-FM
Differenzdruckmanometer
mit pot. freiem Kontakt
Differential pressure gauge
with potential free contact

G 1/4

Ø6,5 FMA30 - FMA70
Ø8,2 FMS90 - FMS110

(DIN 1810 - B Hakenschlüssel mit Zapfen)
(DIN 1810 - B Hook wrench with a pin)

CDE 80/100T
Automatisch zeitgesteuerter Kondensatableiter
Automatic timer controlled condensate drain

Connection Dismantle height Weight

Abmessungen / Dimensions (in mm)

Filter	A	B	ØC	D	Anschluß	Ausbauhöhe	Gewicht (kg)
FMA30	225	82	87	24	G 3/8	130	2,222
FMA50	225	82	87	24	G 1/2	140	2,208
FMA70	290	82	87	24	G 1/2	210	2,673
FMS90	325	116	125	25	G 3/4	190	18,804
FMS110	410	116	125	25	G 1	290	22,377

Maßstab scale		Gewicht / weight	
Datum / date		Name	
30.07.2013	Tal	Benennung / designation	
30.07.2013	Ruff	FMA30 -70/ FMS90 - 110 - Serie PN100	
Norm		- Abmessungen / Dimensions	
Zeichnungs Nr. / drawing no.		Blatt / page	
ZMP-S-100513		1 / 1	
EST GmbH		A2	
Filtrations-Separations-Technik			